

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1403-3

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	STANDARD CATEGORY (miles)			IN- COMP (*=N/A or A/E=exi	MEDIATE USE LIANCE full in-use; h. / evap. ate in-use)	FUEL TYPE				
2007 7GMXT06.2382		LDT: 6001-8500# GVW, 3751-	"LEV II" Low I Vehicle (LEV		EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2		
		5750# ALVW	Venior (EE		120K	150K	•	•	Unleaded)		
No.	No. ECS & SPECIAL FEATURES			APORATIVE I	DISPLAC	EMENT (L)					
1	1 2TWC, 2HO2S(2), SFI, OBD(F)			7GMXR0	176820	22					
*	*			7GMXR0223840							
*	* *			1076 1788 1788 1788 1788 1788					6.2		
*	-	*		*							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1403-2 dated February 15, 2006.

Executed at El Monte, California on this ______9 24 day of June 2006.

Raphael Surnourly Allen Lyons, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *		NMOG or														
CERT	STD	NMOG	14141114		MHC hot-soak; RL [g/mi]=running toss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=miltigram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
0.054	0.054 0.055		CERT CERT	[g/mi]	CO [g/mi]		NC	NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.004	0.030	[g/mi] [g	[g/mi]	10 /	CERT	STD	CERT	STE	CI	ERT S	TD	CERT	STD	CERT	STD	
	@ 50K	0.058	•	0.075	1.8	3.4	0.02	0.05		*	5.	*	*	0.01	0,07	
NAME OF STREET	@ UL	0.058	*	0.090	1.8	4.2	0.02	0.07	•	•	8.	•	•	0.01	0.09	
1100 pp. 12	50°F & 4K	0.125	*	0.150	2.6	3.4	0.03	0.05		* 3	30.	*	*	•	*	
CO [g/ml]				NMHC+NOx [g/mi] CO [g/ (composite) (compo							NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
@ 20°F &	SUK			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	

		J-1	77.51.		1	1							I	1	1
CERT	6.2	SFTP@4	4000 miles	*	*	*	*	0.06	0.40	2.5	10.5	0.12	0.31	2.2	3.5
STD	12.5	SFTP	@ * miles	*	*	*	*	•	*	*	*	*	*	*	•
Evaporative Family		3-Days Diurnal + Hot Soak (grams/test) @ UL			2-Days Diurnal + Hot Soak (grams/test) @ UL			Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL				
			CERT	S	OTE	CERT	,	STD	CER	Г	STD		CERT		STD
	7CMX20176	820	0.48	0	an l	n 35		1 15	0.00		0.05		0.03		n 20

Evaporative Family	3-Days Diurn (grams/te		2-Days Diurn (grams/te		Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ L		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
7GMXR0176820	0.48	0.90	0.35	1.15	0.00	0.05	0.03	0.20	
7GMXR0223840	0.59	0.90	0.36	1.15	0.00	0.05	0.09	D.20	
*	*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	+	ź	
							<u> </u>		

^{*=} not applicable; UL=useful life; PC=passenger car, LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; OCS=oxygen sensor, HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	PHASE-IN STD.	OBDII
					EXH	EVAP		
CADILLAC	ESCALADE EXT AWD	7GMXR0223840	1	6.2	•	•	SFTP	Full
CADILLAC	ESCALADE 2WD	7GMXR0176820	1	6.2	•	*	SFTP	Full
CADILLAC	ESCALADE AWD	7GMXR0176820	1	6.2	*		SFTP	Full
CADILLAC	ESCALADE ESV AWD	7GMXR0223840	1	6.2	•		SFTP	Fuli
CHEVROLET	C1500 SILVERADO CLASSIC 2WD	7GMXR0176820	1	6	*	•	SFTP	Full
CHEVROLET	K1500 SILVERADO CLASSIC 4WD	7GMXR0176820	1	6	±	•	SFTP	Full
GMC	C1500 SIERRA CLASSIC 2WD	7GMXR0176820	1	6	*	*	SFTP	Full
GMC	K1500 SIERRA CLASSIC AWD	7GMXR0176820	1	6	*	*	SFTP	Fulf
GMC	K1500 SIERRA CLASSIC 4WD	7GMXR0176820	1	6	<u> </u>	*	SFTP	Full
GMC	K1500 YUKON DENALI AWD	7GMXR0176820	1	6.2	*	*	SFTP	Full
GMC	K1500 YUKON XL AWD	7GMXR0223840	1	6.2	*		SFTP	Full
GMC	C15 SIERRA 2WD	7GMXR0176820	1	6.2	*		SFTP	Full
GMC	K15 SIERRA AWD	7GMXR0176820	1	6.2	*	*	SFTP	Full